



H03VH-H

Installation Cable 300/300 V with Cu conductors, PVC insulated

APPLICATION

Used in dry and humid places, and as a connecting cables in low mechanical stress.

CONSTRUCTION

Conductors	: Class5 acc.to IEC 60228
Insulation	: PVC compound
Bedding	: -
Armour	: -
Sheath	: -

TECHNICAL CHARACTERISTICS

CPR Class	: Eca
Rated Voltage	: 300/300V
Bending Radius	: 6xD
Max.conductor Temperature	: 70°C
Max.short-circuit Temperature	: 160°C

CORE IDENTIFICATION

According to HD 308 S2

Insulation Color	:
2 core	: White or White/Red

STANDARD

EN 50525-2-11

Sheath Color	:
White	
Other colours available	



Trade Mark of MXN KABLO SANAYİ ve TİCARET LTD.ŞTİ.

H03VH-H

Installation Cable 300/300 V with Cu conductors, PVC insulated

Nominal Cross-Section mm ²	Max Resistance at 20°C Ω/km	Outer Dia (Approx.) mm	Cable Weight (Approx.) kg/km	Current Capacity In Earth A	Current Capacity In Air A
2x0,50	39	2,50x5,00	21	-	9
2x0,75	26	2,70x5,40	26	-	12
2x1	19,5	2,90x5,80	33	-	15